

Date: Wed, 18 Aug 93 04:30:09 PDT
From: Info-Hams Mailing List and Newsgroup <info-hams@ucsd.edu>
Errors-To: Info-Hams-Errors@UCSD.Edu
Reply-To: Info-Hams@UCSD.Edu
Precedence: Bulk
Subject: Info-Hams Digest V93 #988
To: Info-Hams

Info-Hams Digest Wed, 18 Aug 93 Volume 93 : Issue 988

Today's Topics:

Motorola's Bravo Plus Paging Decoder with RS-232 serial port

Send Replies or notes for publication to: <Info-Hams@UCSD.Edu>
Send subscription requests to: <Info-Hams-REQUEST@UCSD.Edu>
Problems you can't solve otherwise to brian@ucsd.edu.

Archives of past issues of the Info-Hams Digest are available
(by FTP only) from UCSD.Edu in directory "mailarchives/info-hams".

We trust that readers are intelligent enough to realize that all text
herein consists of personal comments and does not represent the official
policies or positions of any party. Your mileage may vary. So there.

Date: 18 Aug 1993 10:52:46 GMT
From: swrinde!gatech!howland.reston.ans.net!usenet.ins.cwru.edu!
cleveland.Freenet.Edu!ak667@network.ucsd.edu
Subject: Motorola's Bravo Plus Paging Decoder with RS-232 serial port
To: info-hams@ucsd.edu

In a previous article, mikey@slc.cts.com (Mike Shirley) says:

>RNet(TM) Paging Data Receiver
>o Based on the company's BRAVO Plus(TM) pager technology
>o 20-character message buffer
>o Programmable headers and trailers to let users define specific
> characters at the beginning and end of transmissions
>
>Motorola introduced its RNet(TM) Paging Data Receiver, a board level
>OEM product that received and decodes data broadcast over existing
>paging networks. The receiver operates on 138-174, 435-480 and 900
>MHz channels. Data can be received, decoded and sent at 1200, 2400 or
>9600 baud via a serial RS-232 or TTL interface to the manufacturers
>host equipment. Equipped with three output control ports, the unit
>can be programmed to activate or deactivate various electronic
>switches. The receiver can accommodate any size and number of

>seven-bit ASCII numeric or alphanumeric messages, limited only by the
>speed of the data acceptance from the host computer. The unit's
>multiple addressing capability includes four addresses and can use
>four functions within each address. For Group Call applications,
>receivers programmed with the same Group Call code are alerted to a
>message simultaneously with a single transmission. The receiver
>measures 4.3 x 2.8 x 0.75 inches and is priced at \$130 per unit, based
>on quantity.

Acctually, if this is *THE* Bravo Pager being Advetised around here,
i can get you one for \$49 with a 3month hooookup to the "host machine"
included.. Or is this a new device not yet on the market?

--

- N8YNR (Amateur Radio) -	Jeff S. Garvas	Snail mail all Hate Mail,
- Licensed to transmit -	P.O. Box 25326	Donations, Anonymous "Hi!"
146.82 (Cleveland Area Rptr)	Garfield Hgts. OH	<=-----
ak667@po.cwru.edu (InterNet)	44125	Help! My brain dumped core

End of Info-Hams Digest V93 #988
